

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

 Revision: [33.5](#)

Page 1 of 13

Date of prepared: 01/Jan/2025

Section I – Product and Company Identification

Information of Product 產品信息

Product Identity (used on the label) 產品標識 (用於標籤)	Nickel Metal Hydride Battery/NiMH Rechargeable cell 金屬氢化物镍电池/镍氢可充电电池
---	---

Information of Manufacturer 製造商信息

Manufacturer's Name 製造商名字 Dongguan Chao Ba Batteries Co.,Ltd 东莞超霸电池有限公司	Emergency Telephone Number 緊急聯繫電話 For Emergency Only, Call Chemtrec Within USA and Canada: +1-800-424-9300 Outside USA and Canada: +1-703-527-3887 CCN1012303
Address (Number, Street, City State, and ZIP Code) 聯繫地址 : No. 16 Yinxing Road and No. 2 Yintai Road, Xiegang Town, Dongguan City, Guangdong, China 中国广东省东莞市谢岗镇银兴路16号,银泰路2号	Telephone Number for Information : 諮詢電話 +86 769 86960088
	Date of prepared and revised : 修訂日期 01/Jan/2025

Recommended use of chemicals: 化學物品的建議使用

N.A.

Section II – Hazards Identification 危害識別

GHS Classification: N.A. GHS 分類 (全球化學品統一分類和標籤制度)

Under normal conditions of use, the battery is hermetically sealed. If the electrolyte is leaked, hazardous material may be released. 在正常情況下使用，電池是密封的。但是如果電解液有洩露時，就會出現危害物質

Human Health Effects 人身健康影響

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright@ GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541 Revision: [33.5](#) Page 2 of 13 Date of prepared: 01/Jan/2025

Inhalation 吸入	The electrolyte inhalation can cause respiratory irritation. It could be possibly carcinogen. 吸入電解液會導致呼吸過敏並且有可能致癌
Skin contact 皮膚接觸	The electrolyte can cause skin irritation, chemical burns. Nickel compounds, cobalt and cobalt compounds can cause skin sensitization and an allergic contact dermatitis. 與電解液發生皮膚接觸會導致皮膚刺激與化學燒傷。電池中的含鎳物質以及含鈷物質會刺激皮膚從而導致皮膚過敏，並且可能導致皮膚炎症
Eye contact 眼睛接觸	The electrolyte leaked from the battery cell is strong alkali, can cause severe irritation and chemical burns. 從電池洩露出的電解液具有強鹼性，可以導致嚴重刺激以及化學燒傷
Ingestion 吞入	If the battery is swallowed and opened, or the electrolyte is ingested, the electrolyte irritates the mouth and the throat seriously, may lead to vomiting, nausea, hematemesis, stomach pains and diarrhea. 如果電池被誤吞下並且電池呈暴露狀態，或者電解液被誤服下，電解液會刺激其嘴與喉嚨，可能會造成嘔吐、暈眩、吐血、胃疼以及腹瀉。

Environmental Effects 環境影響

The battery cell remains in the environment. Do not throw it out into the environment.

電池可存在自然界中對環境無污染，但是不能直接丟棄

Specific Hazards 特定危害

As previously described.

綜上所述

Section III – Composition/Information on Ingredients

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

 Revision: [33.5](#)

Page 3 of 13

Date of prepared: 01/Jan/2025

Chemical Name/Common Name 物質名稱	CAS No. CAS 號碼	%/wt 含量 (品質分數 wt%)
Aluminum 鋁	7429-90-5	< 2
Cobalt metal 金屬鈷	7440-48-4	2.5-6.0
Cobalt oxide 氧化鈷	1307-96-6	
Cobalt hydroxide 氫氧化鈷	21041-93-0	
Lithium Hydroxide 氫氧化鋰	1310-65-2	0-4
Manganese 錳	7439-96-5	0-4
Lanthanum 鐳	7439-91-0	<13
Cerium 鈰	7440-45-1	
Neodymium 釹	7440-00-8	
Praseodymium 鐳	7440-10-0	
Nickel hydroxide 氫氧化鎳	12054-48-7	35-55
Nickel oxide 氧化鎳	1313-99-1	
Nickel powder 金屬鎳粉	7440-02-0	
Potassium Hydroxide 氫氧化鉀	1310-58-3	<7
Sodium Hydroxide 氫氧化鈉	1310-73-2	0-4
Zinc metal 金屬鋅	7440-66-6	<3
Zinc oxide 氧化鋅	1314-13-2	
Zinc hydroxide 氫氧化鋅	20427-58-1	
Iron 鐵	7439-89-6	10-25

Section IV – First-aid Measures 急救措施

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

 Revision: [33.5](#)

Page 4 of 13

Date of prepared: 01/Jan/2025

Inhalation 吸入	<p>If electrolyte leakage occurs, cover the victim in a blanket, move to the place of fresh air and keep quiet. Seek medical attention immediately. When dyspnea (breathing difficulty) or asphyxia (breath-hold), give artificial respiration immediately.</p> <p>如果發生電解液洩露並且傷患吸入一定量的電解液，給受傷者鋪上毛毯，並將傷患移到新鮮空氣處。立即尋找醫療救護，當傷患出現呼吸困難或者呼吸停止時，立即給予人工呼吸幫助。</p>
Skin Contact 皮膚接觸	<p>If electrolyte leakage occurs, remove contaminated clothes and shoes immediately. Wash the adherence or contact region with soap and plenty of water. Seek medical attention immediately.</p> <p>如果發生電解液洩露並與傷患皮膚接觸，立即移除粘有電解液的衣物，用大量的水沖洗且附著物和接觸部分，並立即尋求醫療救護。</p>
Eye Contact 眼睛接觸	<p>If electrolyte leakage occurs, immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.</p> <p>如果發生電解液洩露並且接觸到傷患的眼睛，立即用大量的水不停地沖洗眼睛 15 分鐘，並尋求醫療救護</p>
Ingestion 吞入	<p>If battery cell and electrolyte is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.</p> <p>如果電池或電解液被誤服，不要催吐或者給予食物或飲料，要立即尋求醫療救護。</p>

Section V – Fire-fighting Measures 消防措施

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright@ GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

Revision: 33.5

Page 5 of 13

Date of prepared: 01/Jan/2025

Extinguishing Media 滅火介質	Dry sand, chemical powder fire extinguishing medium. 幹砂，化學品滅火劑
Unusual Fire and Explosion Hazards 非尋常火源和爆炸危害	Acrid or harmful fume is emitted during fire. 會有刺激性或者有害氣體在火災過程產生
Special Protective equipment and Precautions for fire-fighters 對於消防員的特別的保護措施和提醒	Fire fighters should wear self-contained breathing apparatus. Burning nickel metal hydride batteries can produce toxic fumes including oxides of nickel, cobalt, aluminum, manganese, lanthanum, cerium, neodymium, and praseodymium. 消防員應穿戴獨立的呼吸設備，而發生燃燒的鎳氫電池會產生含有鎳、鈷、鋁、錳、鐳、鈰、釹、鐳等氧化物的有毒煙霧， Protective equipment written in Section VIII. 防護設備詳見第八部分

Section VI – Accidental Release Measures 意外釋放的措施

Personal Precautions 個人防護	Forbid unauthorized person to enter. Remove leaked materials with protective equipment written in Section VIII. 禁止非授權人員進入洩露現場，處理洩露材料的防護措施詳見第八部分
Environmental precautions 環境防護	Do not throw out into the environment. 不能直接丟棄在環境中
Containment and Clean Up 污染物的清理	Dilute the leaked electrolyte with water and neutralize with diluted sulfuric acid. The leaked solid is moved to a container. The leaked place is fully flushed with water. 用水稀釋洩露的電解液，再用稀硫酸中和。洩露的固體要移至專用的容器中，洩露污染的低於要用水沖洗。

Section VII – Handling and Storage

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541 Revision: [33.5](#) Page 6 of 13 Date of prepared: 01/Jan/2025

Handling	Prevention of user exposure: Not necessary under normal use.
處理	使用者的防護措施：在正常使用下不需要
	Prevention of fire and explosion: Not necessary under normal use.
	火災以及爆炸的防護措施：在正常使用下部需要
	Precaution for safe handling: Do not damage or remove the external tube.
	處理時的安全提醒：不要破壞和移動外部的管道設備
	Specific safe handling advice: Never throw out cells in a fire or expose to high temperatures. Do not soak cells in water and seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or throw down. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. In the case of charging, use only dedicated charger or charge according to the conditions specified by GP Batteries.
	特別的安全處理建議：不要將電池投入在明火以及高溫中。不要將電池浸泡在水或者海水中。不要將電池暴露在強氧化性的環境中。不要對電池進行高強度的機械碰撞或者投擲，不要對電池進行解剖彎曲變形。不要短接正負極，充電時，只是用由 GP 所提供的充電器或者充電方法
Storage	Storage conditions (suitable to be avoided): Avoid direct sunlight, high temperature, high humidity.
儲存	The cells and batteries shall not be stored in high temperature ,the maximum temperature allowed is 60°C for a short period during the shipment. Otherwise the cells maybe leakage and can result in shortened cycle life.
	存儲條件：避免直接的日曬、高溫、高濕度。電池不能存儲在高溫環境中，在短期運輸過程中，最高溫度為60攝氏度，如果違反儲存建議，電池有可能出現漏泄情況並導致循環壽命減少
	Incompatible products: Conductive materials, water, seawater, strong oxidizers and strong acids
	Packing material (recommended, not suitable): insulated and tear-proof materials are recommended.
	不能一起儲存的產品：導電材料、水、海水、強氧化劑、強酸
	包裝所用材料（建議）：絕緣並且防撕裂的材料

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

Revision: 33.5

Page 7 of 13

Date of prepared: 01/Jan/2025

Section VIII – Exposure Controls/Personal Protection 暴露控制和人身保護
Engineering Control 工程控制

No engineering measure is necessary during normal use. If internal cell materials are leaked, the information below will be useful.

在正常使用情況下不需要工程控制手段。如果電池內部材料洩露，以下資訊可提供參考。

Exposure Control Limit 暴露控制界限

Common Chemical Name / General Name 化學物質名稱	OSHA PEL	ACGIH TLV
Aluminum metal (as Al) 金屬鋁	TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)	-
Cobalt metal (As Co) 金屬鈷	TWA 0.1 mg/m ³	TWA 0.02 mg/m ³
Lithium Hydroxide 氫氧化鋰	-	-
Manganese compounds (as Mn) 錳化物	(Ceiling) 5 mg/m ³	TWA 0.02 mg/m ³ (resp.)
Nickel, metal and insoluble compounds 鎳 (金屬以及不溶物)	(as Ni) TWA 1 mg/m ³	Elemental 元素含量: 1.5mg/m ³ (IHL); Insoluble inorganic compounds 不溶有機物: 0.2mg/m ³ (IHL)
Potassium Hydroxide 氫氧化鉀	-	-
Sodium Hydroxide 氫氧化鈉	2 mg/m ³ TWA	(Ceiling) 2 mg/m ³
Zinc oxide 鋅化物	Respirable fraction:呼吸閾值 5 mg/m ³	Respirable fraction: 呼吸閾值 2 mg/m ³

TWA – Time Weighted Average 時間加權平均值

ACGIH TLV: American Conference of Governmental Industrial Hygienists Threshold Limit Value 美國政府工業衛生學家會議所提供暴露閾值

OSHA PEL: Occupational Safety & Health Administration Permissible Exposure Limit 職業安全和健康署所允許暴露閾值

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

Revision: 33.5

Page 8 of 13

Date of prepared: 01/Jan/2025

Personal protective equipment 個人防護設備

Respiratory protection: Protective mask 呼吸設備：防護面罩

Hand protection: Protective gloves 手防護：防護手套

Eye protection: Protective glasses designed to protect against liquid splashes

眼睛防護：防止液體飛濺的防護眼鏡

Skin and body protection: Working clothes with long sleeve and long trousers

皮膚及身體防護：長袖長褲的工作服

Section IX – Physical and Chemical Properties 物理與化學性質

Appearance 外觀 Solid, Cylindrical Shape, Metallic color 固體、圓柱形、金屬顏色	Odor 氣味 Odorless 無 Odor Threshold 氣味閾值 N.A.
pH N.A.	Melting point/freezing point 熔點/凝固點 N.A.
Initial boiling point and boiling range 開始沸騰溫度點與沸騰溫度範圍 N.A.	Flash point 閃點 N.A.
Evaporation rate 蒸發率 N.A.	Flammability (solid, gas) 可燃性 (固體、氣體) N.A. Upper/lower flammability or explosive limit 可燃上限與下限以及爆炸極限 N.A.
Vapor pressure 蒸汽壓 N.A.	Vapor density 氣體密度 N.A.
Relative density 相對密度 N.A.	Solubility 溶解度 Insoluble in water 不溶于水中
Partition coefficient: n-octanol/water 分配係數 (正辛醇/水) N.A.	Auto-ignition temperature 自燃溫度 N.A.
Decomposition temperature 分解溫度 N.A.	Viscosity 粘度 N.A.

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

Revision: 33.5

Page 9 of 13

Date of prepared: 01/Jan/2025

Section X – Stability and Reactivity

Stability 穩定性	Stable under normal use 在正常使用中穩定
Possibility of hazardous reactions 可能存在的危險反應	<p>By misuse of a battery cell or the like, oxygen or hydrogen accumulates in the cell and the internal pressure rises. These gases may be emitted through the gas release vent. When fire is near, these gases may take fire.</p> <p>When a battery cell is heated strongly by the surrounding fire, acrid or harmful fume may be emitted.</p> <p>如果不正當使用電池時，會導致氧氣和氫氣在電池內部聚集從而導致內壓上升，氣體會通過氣壓閥釋放出來，當此次有明火靠近時，會引起氣體燃燒。當電池被加熱劇烈時，會導致刺激性和有害的氣體釋放</p>
Conditions to avoid 需避免的情況	<p>Direct sunlight, high temperature and high humidity</p> <p>直接日曬、高溫、高濕度</p>
Materials to avoid 需避免的材料	<p>Conductive materials, water, seawater, strong oxidizers and strong acids</p> <p>導電材料、水、海水、強氧化劑、強酸</p>
Hazardous decomposition products 分解時的有害產物	<p>Acrid or harmful fume is emitted during fire.</p> <p>在燃燒中會產生有刺激性的有害氣體</p>

Section XI – Toxicological Information 毒理學信息

There is no toxicity data for Nickel Metal Hydride Battery. Under normal conditions of use, the battery is non-toxic.

沒有關於鎳氫電池的毒理學資訊，在正常使用條件下，電池是無毒的。

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541

Revision: 33.5

Page 10 of 13

Date of prepared: 01/Jan/2025

Section XII – Ecological Information 生態學信息

Persistence/degradability : 可持續性和可降解性 :

Since a battery cell and the internal materials remain in the environment, do not bury or throw out into the environment. 由於電池以及內部材料仍然保留在環境中，不要丟棄以及埋藏電池與大自然中

Section XIII – Disposal Considerations 處理方法

Recommended methods for safe and environmentally preferred disposal : 建議使用的對環境友好的處理方法

Product (waste from residues) 產品 (殘留廢棄物)

Do not throw out a used battery cell. Recycle it through the recycling company.

不要丟棄已使用過的電池，應將其給相應的回收公司

Contaminated packaging 有污染的包裝

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates them, dispose them as industrial wastes subject to special control.

在正常使用下不會出現包裝以及放置容器出現被污染的情況。當電池內部的材料洩漏時並污染其包裝容器，

可將被污染的包裝容器按特定的工業廢物處理

Section XIV – Transport Information 運輸資訊

Regulatory Body 條例主題	Special Provisions 特定條例
ADR	295 – 304, 598
IMO	UN 3496 SP117 and SP963
UN	UN 3496
US DOT	49 CFR 172, 102 Provision 130
IATA	A199

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright@ GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541 Revision: [33.5](#) Page 11 of 13 Date of prepared: 01/Jan/2025

Form of Transportation 運輸方式	UN No.	UN Proper Shipping Name UN 運輸名稱	Transport Hazard Class 運輸危害等級	Packing Group Number 包裝組別號碼	Environmental Hazards 環境危害	Guidance Transport in bulk 運輸指引	Special Precaution 特別提示
Sea 海運	3496	BATTERIES, NICKEL-METAL HYDRIDE	9	-	No	According to ANNEX II of MARPOL 73/78 and the IBC Code	SP117 & SP963

a) In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in “strong outer packaging” that prevents spillage of contents. All original packaging for GP nickel metal hydride batteries has been designed to be compliant with these regulatory concerns.

一般來講，所有電池在所有運輸過程中（海陸空運輸）都必須安全地包裝。出於安全管理的考慮，安全包裝必須避免電池的短路問題以嚴重外露的問題，這是保證避免電池以及電池內部的材料洩露。所有的 GP 鎳氫電池均會遵守其管理規定來進行包裝。

GP nickel metal hydride batteries (sometimes referred to as “Dry cell” batteries) are not defined as dangerous goods under the IATA Dangerous Goods Regulations 66th edition 2025, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations as they are compliant with the requirements contained in the following special provisions.

Remark: “N.A.” is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541 Revision: [33.5](#) Page 12 of 13 Date of prepared: 01/Jan/2025

在國際空運協會(IATA)危險貨物條例第 66 版 (2025) 、國際民航管理局(ICAO)的技術條例以及美國危險化學品管理條例 (49CFR) 的規定當中 GP 鎳氫電池 (也被稱作 “乾電池”) 是不作為危險貨物。電池也只有在遵守相關的特定規定情況下才能不列入危險貨品中。

In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words “not restricted” and the Special Provision number A199 be provided on the air waybill, when an air waybill is issued.

除此之外，國際空運協會(IATA)危險貨物條例和國際民航管理局(ICAO)的技術條例均要求 “不作限制” ，同時要注意針對特別條例 A199 (美國運輸局) ，需要在運貨單中進行說明

b) International Maritime Organization (IMO) IMDG Code [41-22](#) regulated these products as UN 3496 BATTERIES, NICKEL METAL HYDRIDE, class 9 dangerous goods with Special Provision 117 and 963 assigned

國際海事組織:國際海運危險品法規 [41-22](#) 其產品號碼為：UN 3496 BATTERIES, NICKEL METAL HYDRIDE 为第九級危險品, 在特殊例 117 和 963 中为非危險品

SP117

Only regulated when transported by sea.

SP963

Nickel-metal hydride button cells or nickel-metal hydride cells or batteries packed with or contained in equipment are not subject to the provisions of this Code.

在設備中的鎳氫鈕扣電池、鎳氫電池或者電池組不受此特殊條例管理

Nickel metal hydride batteries are handled according to the updated version of Special Provisions including SP 117 & SP 963 of IMDG (International Maritime Dangerous Goods) Code.

镍金属氢化物电池按照 IMDG (国际海运危险货物) 规则 SP 117 和 SP 963 等特殊规定的更新版本进行处理。

The batteries shall be securely packed and protected from short circuit.

电池应包装牢固，并防止短路。

Remark: “N.A.” is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved

Safety Data Sheet for Nickel Metal Hydride Battery

Document Number: RRS0541 Revision: [33.5](#) Page 13 of 13 Date of prepared: 01/Jan/2025

Nickel metal hydride button cells/batteries or batteries contained in/packed with equipment are not regulated as dangerous goods.

镍金属氢化物纽扣电池/电池或设备中包含/包装的电池不作为危险品进行监管。

When gross mass of nickel-metal hydride batteries per container is 100 Kg more then they are subjected to three requirements:

当每箱中的镍金属氢化物电池的总质量超过 100 公斤时，它们需要满足三个要求：

- a. Dangerous goods declaration
- a. 危险货物申报
- b. Inclusion of dangerous goods manifest placed on board vessel
- b. 列入船上的危险货物清单
- c. Stowage "Away from the sources of heat".
- c. 堆放“远离热源”。

Section XV – Regulatory Information 調整資訊

Special requirement be according to the local regulations.

特殊需求根據當地規則調整

Section XVI – Other Information 其他資訊

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

本化學品安全技術說明書中的資料只針對本產品的特定材料。

Remark: "N.A." is indicated if not applicable.

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Copyright© GP Energy Tech International Pte. Limited – All rights reserved